

How to order GSPS 60kW - Configurable Power solu-

G	SPS	10	4500			
Series Name		Output	Output	Interface Options	AC Input Options	Accessories Options
Front Panel Type		Voltage	Current		3P208 (Three Phase 170~265VAC)	M - Printed *User Manual
Empty: standard		(0~10V)	(0~1500A)		3P480 (Three Phase 342~528VAC)	* User Manual & GUI are available on the website
B: Blank Front Panel (ATE version)						

Interface Options (Factory installed)

LAN (LX) 1.5 compliant with Multi-Drop capability)- built-in
 USB 2.0 compliant with Multi-Drop capability - built-in
 RS-232/RS-485 - built-in
 Isolated Analog Program/Monitor Interface (5V/10V Pgm/Mon with 600V isolation) - built-in
 IEEE (488.2 & SCPI compliant with Multi-Drop capability installed)
 Modbus-TCP
 EtherCAT

P/N

-
 -
 -
 -
 IEEE
 MDBS
 ECAT

Power (kW)	30kW	45kW	60kW
Voltage (VDC)	Current (A)		
0~10V	0~3000	-	0~4500
0~20V	0~1500	0~2250	0~3000
0~30V	0~1020	0~1530	0~2040
0~40V	0~750	0~1125	0~1500
0~50V	0~600	0~900	0~1200
0~60V	0~510	0~765	0~1020
0~80V	0~390	0~585	0~780
0~100V	0~300	0~450	0~600
0~150V	0~204	0~306	0~408
0~200V	0~150	0~225	0~300
0~300V	0~102	0~153	0~204
0~400V	0~78	0~117	0~156
0~500V	0~60	0~90	0~120
0~600V	0~51	0~76.5	0~102