Digital Filter App

GDS-1000B Series

USER MANUAL

GW INSTEK PART NO. V1.00





This manual contains proprietary information, which is protected by copyright. All rights are reserved. No part of this manual may be photocopied, reproduced or translated to another language without prior written consent of Good Will company. The information in this manual was correct at the time of printing. However, Good Will continues to improve products and reserves the

rights to change specification, equipment, and maintenance procedures at any time without notice.



Table of Contents

GETTING STARTED	5
App Overview	5
Installing Optional A	pps 6
Uninstalling Optiona	l Apps8
Running Applications	s9
USING THE DIGITAL FILTER	10





GETTING STARTED

App Overview

Background	The GDS-1000B comes pre-installed with a number of apps. Optional apps can also be downloaded from the GW Instek website free of charge at www.gwinstek.com .		
Included Applications	Go/No-Go	The Go/No-Go application can be used to set threshold boundaries for input signals. Go/No-Go tests to see if a waveform will fit inside a user-specified maximum and minimum amplitude boundary (template).	
	Mount Remote Disk*	This app allows the scope to mount a network share drive.	
	* 4 channel models only.		
Optional Applications	Digital Filter	Adds a digital low or high pass filter to any of the input channels. Each filter can have a user-defined cutoff frequency set.	
	DVM	The DVM application displays a digital voltage meter readout that floats on the top left-hand side of the screen.	



Data Log	The Data Log app will log	
	waveform data and/or	
	screenshots at set intervals for set	
	duration of time.	

Installing Optional Apps

Background

The GDS-1000B has optional software apps that can be installed to add additional functionality to the DSO.

Steps

- 1. Download the Digital Filter App zip file from the GW Instek website.
- 2. Unzip the Digital Filter App zip file.

The App zip file contains the APP installation file (DigitalFilter_1KB.gz) and this user manual.

- 3. Copy the installation file (DigitalFilter_1KB.gz) onto a USB flash drive.
- Insert the USB flash drive that contains the DigitalFilter_1KB.gz file into the front panel USB A port of the GDS-1000B.



5. Press the *Utility* key then the *File Utilities* soft-key.





- 6. Use the *Variable* knob and *Select* key to navigate to the DigitalFilter_1KB.gz file on the USB drive.
- VARIABLE

 Select
- 7. Press the *Select* key to start the installation.
- 8. The installation will complete in a few seconds. When finished a pop-up message will appear asking you to restart the GDS-1000B.
- 9. Restart the GDS-1000B.



Uninstalling Optional Apps

Background

Any optional apps that were installed can be uninstalled from the APP menu. Pre-installed apps, such as the Go-NoGo app cannot be uninstalled.

Steps

1. Press the APP key.



2. Highlight the app that you want to uninstall with the *Variable* knob.



3. Press *Uninstall* twice from the side menu to uninstall the selected app.

Uninstall

x2



Running Applications

Background

The APP function can host a number of different applications, some of which as pre-installed and some of which are installed as optional extras.

Panel Operation

1. Press the *APP* key.



2. Press *APP* from the bottom menu.



3. Scroll through each application using the *Variable* knob.



4. Select an application by pressing the *Select* key *twice*.



USING THE DIGITAL FILTER

Background


The Digital Filter app is a digital high or low pass filter with a selectable cutoff frequency. The digital filter can be applied to each channel individually or together using the tracking functionality.

Basic Features:

- High pass or low pass filtering of analog channels.
- Selectable cutoff frequencies.
- Tracking function



Example



Digital filter type or status

CH1 input: 2Vpp 1kHz square wave, low pass filter with 1kHz cutoff frequency.

CH2 input: 2Vpp 1kHz square wave, high pass filter with 1kHz cutoff frequency.

Panel Operation

 Choose the Digital filter application from the APP menu. See page 9.



Set Source

2. Select a source channel by pressing CH1 Filter, CH2 Filter, CH3 Filter or CH4 Filter.



- 3. From the side menu press *Filtering* and turn on.
- 4. Press *Filter Type* and select low or high pass filter.







5. If Low Pass was selected, press *Upper Limit* to set the low pass cutoff frequency. Likewise if High Pass was selected, press *Lower Limit* to set the high pass cutoff frequency. Only one option will be available at a time.



Upper Limit $1Hz \sim 500MHz$ Lower Limit $1Hz \sim 500MHz$

Tracking

6. Press *Tracking* if you want the settings of the digital filter on each channel to be the same. When a setting is changed on one channel, it is reflected on the other channels.





The digital filter settings will still apply to the relevant input signals after leaving the app, unless turned off.