
PXI-5404

Specifications

2023-08-09



Contents

PXI-5404 Specifications.....	3
------------------------------	---

PXI-5404 Specifications

Conditions

Specifications are valid under the following conditions unless otherwise noted:

- Ambient temperature range of 0 °C to 50 °C
- Output voltage amplitudes with a 50 Ω load
- SINE out voltage amplitude of 2 V_{pk-pk} with a 50 Ω load
- CLOCK out level of 5 V
- External calibration performed between 18 °C and 28 °C

Typical specifications were determined on a small sampling of PXI-5404 waveform generators.

CH 0 Outputs

Both CH 0 outputs generate the same frequency simultaneously.

Number of outputs	1 sine
	1 clock

CH 0 SINE Out

Connector type	SMB male
Frequency range	9 kHz to 105 MHz
Frequency resolution	1.07 μ Hz

Phase range	0° to 359.978°
Phase resolution	16,384 steps including endpoints (~ 0.022°)
Output impedance	50 Ω , nominal
Output protection	10 V RMS
Sample rate	300 MS/s
Amplitude range	
Open load	4 V pk-pk to 2 V pk-pk
50 Ω load	2 V pk-pk to 1 V pk-pk
Amplitude resolution	2,048 steps including endpoints
Amplitude accuracy (50 kHz)	$\pm 1\%$
Amplitude passband flatness (relative to the amplitude at 50 kHz)	± 0.2 dB
Vertical resolution (open load)	
4 V pk-pk	12 bits
2 V pk-pk	11 bits
Bandwidth (0.2 dB)	105 MHz
Filter	Analog, 7-pole elliptical

Table 1. Signal to Noise and Distortion (SINAD)

Frequency	SINAD (dB), Typical
1 MHz	+51
10 MHz	+48
20 MHz	+45
50 MHz	+42
100 MHz	+42

Table 2. Spurious-Free Dynamic Range (SFDR) with Harmonics

Frequency	SFDR with Harmonics (dBc), Typical
1 MHz	-55
10 MHz	-54
20 MHz	-49
50 MHz	-45
100 MHz	-53

Table 3. Total Harmonic Distortion (THD)

Frequency	THD (dB), Typical
1 MHz	-50
10 MHz	-47
20 MHz	-40
50 MHz	-35
100 MHz	-30
Average noise density	
0.126 $\mu\text{V RMS}/\sqrt{\text{Hz}}$	
-125 dBm/Hz	

CH 0 CLOCK Out

Connector type	SMB male
----------------	----------

Frequency range	DC to 105 MHz
Frequency resolution	1.07 μ Hz
Phase range	0° to 359.978°
Phase resolution	16,384 steps including endpoints (~ 0.022°)
Output impedance	50 Ω , nominal
Output protection	+8 V to -4 V

Table 4. Output Current (Source or Sink)

Voltage Level	Current (mA), Typical
5.0 V	120
3.3 V	72
1.8 V	48

Table 5. Amplitude (Open Load)

Voltage Level	Amplitude (V)			
	VOL		VOH	
	Minimum	Maximum	Minimum	Maximum
5.0 V	-0.10	0.40	4.00	5.30
3.3 V			2.60	3.70
1.8 V			1.40	2.20

Table 6. Amplitude (50 Ω Load)

Voltage Level	Amplitude (V)			
	VOL		VOH	
	Minimum	Maximum	Minimum	Maximum
5.0 V	-0.10	0.20	2.00	2.65
3.3 V			1.30	1.85

Voltage Level	Amplitude (V)			
	VOL		VOH	
	Minimum	Maximum	Minimum	Maximum
1.8 V			0.70	1.10
Rise/fall time (50 Ω load)		4 ns		
Duty cycle range		25% to 75%		
Duty cycle accuracy				
30% to 70%		±2%, typical		
25% and 75%		±4%, typical		

PFI 0 I/O

Connector type	SMB male
Direction	Bidirectional
Frequency range	DC to 20 MHz
Input signal	
Destinations	PXI_Trig <0..7> (backplane connector) REF OUT (front panel connector) Start Trigger
Input resistance	1 k Ω \pm 1%
Input protection	+8 V to -4 V

VIH	2.0 V
VIL	0.8 V
Output signal	
Sources	PXI_CLK10 (backplane connector) Sample Timebase Clock (60 MHz) divided by N ($3 \leq N \leq 255$) REF IN (front panel connector) PXI_Trig <0..7> (backplane connector) PXI Star Trigger (backplane connector) CH 0 CLOCK out (front panel connector) Software Trigger Start Trigger
Output impedance	$50 \Omega \pm 5\%$
Output protection	+6 V to -1 V
Minimum VOH	
Open load	4.0 V
50 Ω load	2.0 V
Maximum VOL	
Open load	0.4 V
50 Ω load	0.2 V

Rise/fall time	4 ns
----------------	------

REF IN

Connector type	SMB male
Frequency range	
Phase-Locked Loop (PLL) Reference destination	1 MHz to 20 MHz
All other destinations (besides PLL Reference)	200 kHz to 30 MHz
Destinations	PLL Reference REF OUT (front panel connector) PFI 0 (front panel connector) PXI_TRIG <0..7> (backplane connector)
Input impedance	1 k Ω \pm 1%
Input protection (sine or square wave)	12 V pk-pk \pm 5 V DC
Amplitude (sine or square wave)	300 mV pk-pk to 5 V pk-pk
Input coupling	AC

REF OUT

Connector type	SMB male
Frequency range	DC to 20 MHz

Sources	PXI_CLK10 (backplane connector) Sample Timebase Clock (60 MHz) divided by N ($3 \leq N \leq 255$) REF IN (front panel connector) PXI_Trig <0..7> (backplane connector) PXI Star Trigger (backplane connector) CH 0 CLOCK out (front panel connector) PFI 0 (front panel connector) Software Trigger Start Trigger
Output impedance	$50\ \Omega \pm 5\%$
Output protection	+6 V to -1 V
VOH	
Open load	4.0 V
50 Ω load	2.0 V
VOL	
Open load	0.4 V
50 Ω load	0.2 V
Rise/fall time (50 Ω load)	4 ns

Start Trigger

Sources	PFI 0 (front panel connector) PXI_Trig<0..7> (backplane connector) PXI Star Trigger (backplane connector) Software Immediate (Does not wait for a trigger.)
Mode	Continuous
Trigger detection	Edge (rising)
Minimum pulse width	10 ns
Trigger to SINE output delay	250 μ s, typical

Sample Clock

Frequency	300 MS/s
Average phase noise density	-112 dBc/Hz

Phase-Locked Loop (PLL) Reference

Sources	PXI_CLK10 (backplane connector) REF IN (front panel connector) PXI_TRIG <0..7> (backplane connector)
---------	--

	None (The PLL is not used.)
Frequency accuracy	When using the PLL, the frequency accuracy of the PXI-5404 is solely dependent on the frequency accuracy of the PLL Reference source.
Lock time	200 ms, typical
Frequencies	3 MHz to 20 MHz in 1 MHz increments
Frequency locking range	± 50 ppm
Duty cycle range	30% to 70%

Internal Clock

Clock source	The clock circuitry of the PXI-5404 can either be locked to a reference signal using the PLL or use an onboard frequency reference, specifically the Internal Clock.
Frequency accuracy	± 25 ppm, maximum ± 11 ppm, typical
Frequency temperature coefficient	± 0.4 ppm/ $^{\circ}\text{C}$

External Calibration

Calibration interval	Specifications valid within one year of external calibration
----------------------	--

Warm-up time	15 minutes
--------------	------------

Power

+3.3 V rail	1 A
+5 V rail	550 mA
+12 V rail	180 mA
-12 V rail	50 mA

Environment

Operating temperature	0 °C to 50 °C
Storage temperature	-20 °C to 70 °C

Physical

Dimensions	3U, one-slot, PXI/cPCI module
	21.6 cm × 2.0 cm × 13.0 cm (8.5 in. × 0.8 in. × 5.1 in.)
Weight	175 g (6.1 oz)

Compliance and Certifications

Safety Compliance Standards

This product is designed to meet the requirements of the following electrical equipment safety standards for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 61010-1, CSA C22.2 No. 61010-1



Note For safety certifications, refer to the product label or the [Product Certifications and Declarations](#) section.

Electromagnetic Compatibility

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- EN 61326-1 (IEC 61326-1): Class A emissions; Basic immunity
- EN 55011 (CISPR 11): Group 1, Class A emissions
- EN 55022 (CISPR 22): Class A emissions
- EN 55024 (CISPR 24): Immunity
- AS/NZS CISPR 11: Group 1, Class A emissions
- AS/NZS CISPR 22: Class A emissions
- FCC 47 CFR Part 15B: Class A emissions
- ICES-001: Class A emissions



Note In the United States (per FCC 47 CFR), Class A equipment is intended for use in commercial, light-industrial, and heavy-industrial locations. In Europe, Canada, Australia, and New Zealand (per CISPR 11), Class A equipment is intended for use only in heavy-industrial locations.



Note Group 1 equipment (per CISPR 11) is any industrial, scientific, or medical equipment that does not intentionally generate radio frequency energy for the treatment of material or inspection/analysis purposes.



Note For EMC declarations, certifications, and additional information, refer to the [Product Certifications and Declarations](#) section.

Product Certifications and Declarations


Refer to the product Declaration of Conformity (DoC) for additional regulatory compliance information. To obtain product certifications and the DoC for NI products, visit ni.com/product-certifications, search by model number, and click the appropriate link.

Environmental Management


NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial to the environment and to NI customers.

For additional environmental information, refer to the **Engineering a Healthy Planet** web page at ni.com/environment. This page contains the environmental regulations and directives with which NI complies, as well as other environmental information not included in this document.

EU and UK Customers

-  **Waste Electrical and Electronic Equipment (WEEE)**—At the end of the product life cycle, all NI products must be disposed of according to local laws and regulations. For more information about how to recycle NI products in your region, visit ni.com/environment/weee.

电子信息产品污染控制管理办法（中国 RoHS）

-  **中国 RoHS**— NI 符合中国电子信息产品中限制使用某些有害物质指令(RoHS)。关于 NI 中国 RoHS 合规性信息，请登录 ni.com/environment/rohs_china。(For information about China RoHS compliance, go to ni.com/environment/rohs_china.)